

# PROJECT DATA

CONSTRUCTION TYPE: SEISMIC DESIGN CATEGORY:

12,611 SF LOT AREA: EXISTING LOT COVERAGE: 20% (2,530/12,611)
PROPOSED LOT COVERAGE: 24% (2,994/12,611)
ALLOWABLE LOT COVERAGE: 40% (5,044/12,611) EXISTING LOT COVERAGE:

MAXIMUM PROPOSED BUILDING HEIGHT w/o GUARDRAIL: 24-3\*
MAXIMUM PROPOSED BUILDING HEIGHT w/ 42\* GUARDRAIL: 28-6\*

PARKING SPACES: 3 (EXISTING)
ADU IS EXEMPT FROM THE REQUIREMENT TO ADD A
PARKING SPACE, SITE IS LOCATED LESS THAN 0.5 MILES
FROM A BUS STOP AT 2053 QUEENS LN.

FIRE SPRINKLERS: ADU IS EXEMPT FROM THE REQUIREMENT TO ADD FIRE SPRINKLERS. EXISTING PRIMARY RESIDENCE IS NOT REQUIRED TO HAVE FIRE SPRINKLERS. (SB 1089, CAL FIRE INFORMATION BULLETIN 21-005)

SQUARE FOOT CALCULATIONS: 1ST STORY: +464 SF LOFT: +120 SF TOTAL SF OF PROPOSED ADU: 584 SF

#### PROJECT DESCRIPTION

AN ACCESSORY DWELLING UNIT IN THE BACK YARD OF AN EAST TWO PRAMEY RESIDENCE, BOTHERING OF AN EAST TWO PRAMEY RESIDENCE, BOTHERING COMPRISED OF A GREAT FROOM WHITE AS MALE KITCHER AND A LOFF, ABATHEROOM, A BEDROOM, AND A BACKOP, THE ADD USEPPORTS A RACOP ECK, AT THE BEAR OF THE PRAMEY RESIDENCE. LOCATED IN A WILLDARD WERN THE PRAMEY RESIDENCE. LOCATED IN A WILLDARD WIRRAND FAULT OF THE PROPERTY O

THIS APPLICATION SEEKS A CONDITIONAL USE PERMIT FOR THE FOLLOWING:

1) WINDOWS FACING THE REAR EXTENDING HIGHER THAN 10' ABOVE GRADE

2) A ROOF BECK
3) LACKING STEPBACKS OVER 16' ABOVE GRADE

SEE ATTACHED LETTER IN SUPPORT OF THE FINDING THAT THE PROPOSED ADU WILL NOT, UNDER THE CIRCUMSTANCES OF THE PARTICULAR CASE, BE DETRIMENTAL TO THE PUBLIC WELFARE OR INJURIOUS TO PROPERTY OR IMPROVEMENTS IN THE NEIGHBORHOOD.

THE PROPOSED ADU'S WINDOWS, ROOF DECK, AND LACK OF STEPBACKS ARE NOT DETRINENTAL TO NEIGHBORS OF PUBLIC WELFARE BECAUSE THE SUBJECT PROPERTY BORDERS AN OPEN SPACE TO THE REAR AND IS LOWER IN ELEVATION THAN THE PIRST FLOOR OF ADJACENT NEIGHBORS.

## PROJECT DIRECTORY

ARCHITECT Arkin Tilt Architects 1101 Eighth Street, Suite 180 Berkeley, CA 94710 E: tom@wrkinell.com C: 513.722.6231 T: 510.528.9630

STRUCTURAL ENGINEER


## DRAWING INDEX

A0.1 COVER SHEET SITE PLAN & ROOF PLAN

A1.1 SITE PLAN, SECTIONS, & PERSPECTIVE A1.2 EROSION CONTROL PLAN


A2.1 FLOOR PLANS


A3.1 EXTERIOR ELEVATIONS A4.1 BUILDING SECTIONS




4 SITE AERIAL PERSPECTIVE SCALE: N.T.S.

LANDSCAPE IMAGE FROM GOOGLE EARTH







A1.2 SCALE: 1/8" = 1'-0'



4 TREE PROTECTION


A1.2 SCALE: SCALE: N.T.S.





ENTRENCHMENT DETAIL N.T.S. If more than one fiber roll is placed in a row, the rolls must be overlapped, not abutted.

3 FIBER ROLLS A1.2 SCALE: SCALE: N.T.S.




ACTUAL LAYOUT DETERMINED IN FIELD.

2. THE CONCRETE WASHOUT SIGN
SHALL BE INSTALLED WITHIN
30 FT, OF THE TEMPORARY
CONCRETE WASHOUT FACILITY.

DETAIL FROM CALIFORNIA STORMWATER BMP HANDBOOK (07/2012)

1 STOCKPILE PROTECTION A1.2 SCALE: SCALE: N.T.S.




SHEET NOTES

1. Erosion Control Point of Contact: TBD upon contractor selection

18; Use temporary erosion controls to stabilize all denuded areas until permanent erosion controls are established.

20. Use of plastic sheeting between October 1 and April 30 is not acceptable, unless for use on stockpiles where the stockpile is also protected with fiber rolls containing the base of the stockpile. 21. Trap sediment on-site, using BMPs such as sediment basins or trap earthen dikes or berms, silt fences, check dams, soil blankets or mats, covers for soil stock piles, etc.


 Protect adjacent properties and undisturbed areas from construction impacts using vegetative buffer strips, sediment barriers or filters, dikes mulching, or other measures as appropriate. 24. Tree protection shall be in place before any de excavating or grubbing is started.




SP-1. STOCKPILE PROTECTION




2 CONCRETE WASTE MGMT. A1.2 SCALE: SCALE: N.T.S.









3 NORTH WEST ELEVATION A3.1 SCALE: 1/4" = 1'-0" FIRE RESISTANT EXTERIOR SLIDING SHUTTER

