NEW SINGLE FAMILY HOME TBD 10TH STREET, MONTARA, CA

TYPE OF OCCUPANCY:

CONSTRUCTION TYPE:

	ABBR	EVIATI	IONS
@	AT	N	NORTH
#	NUMBER	(N)	NEW
AB	ANCHOR BOLT	N/A	NOT APPLICABLE NOT AVAILABLE
A/C	AIR CONDITIONER	NA NIC	NOT AVAILABLE NOT IN CONTRACT
AFF	ABOVE FINISHED FLOOR	NOM	NOT IN CONTRACT NOMINAL
APPROX	_	NR	NON-RATED
ASF	ABOVE SUBFLOOR	NSF	NET SQUARE FEET
AS	ABOVE SLAB	NTS	NOT TO SCALE
BLDG	BUILDING	0	OVEN
BLK BLKG	BLOCK BLOCKING	OA	OVERALL
BM	BEAM	OC	ON CENTER
BOT	BOTTOM	OD	OUTSIDE DIAMETER OR
			OVERFLOW DRAIN
CAB	CABINET	OFF	OFFICE
CB	CATCH BASIN	OPNG	OPENING
CL	CENTERLINE	OH	OVERHANG
CLG	CEILING	O/H	OVERHEAD
CLST	CLOSET	OPP	OPPOSITE
CMU CO	CONCRETE MASONRY UNIT CLEAN OUT	PL	PLATE OR PROPERTY LINE
COL	COLUMN	PLYWD	PLYWOOD
CONC	CONCRETE	PR	PAIR
CONT	CONTINUOUS	PT	POINT OR PRESSURE TREATE
	DRYER	R	RADIUS
D DBL	DOUBLE	RAG	RETURN AIR GRILLE
DEPT	DEPARTMENT	RD	ROOF DRAIN
DEG	DEGREES	REF	REFRIGERATOR
DIA	DIAMETER	REINF	REINFORCED OR
DIM	DIMENSION	INCHINE	REINFORCEMENT
DN	DOWN	REQ'D	REQUIRED
DR	DOOR	REV	REVISION
DS	DOWNSPOUT	RHB	RADIANT HEATING BOILER
DW	DISHWASHER	RM	ROOM
DWG	DRAWING	RO	ROUGH OPENING
(E)	EXISTING	ROW	RIGHT-OF-WAY
EA	EACH	S	SOUTH
ELEC	_	SB	SETBACK
_	ELEVATION	SCHED	SCHEDULE
	ENGINEER	SD	SMOKE DETECTOR/STORM
	EQUIPMENT		DRAIN
EXT		SF	SQUARE FEET OR SQUARE FO
FAU	FORCED AIR UNIT	SH	SHOWER HEAD
FAR		SHT	SHEET
FD	FLOOR DRAIN	SHWR	
FF	FINISHED FLOOR	SHTG	_
FIN	FINISH	SIM	SIMILAR
FL	FLOOR	SL SPEC	SLIDING SPECIFICATION
FLUOR		SPEC	SQUARE
FOUND		SS	SANITARY SEWER
FP	FIREPLACE	STL	
FT			STORAGE
FTG			STRUCTURAL
FURN	FURNACE	SUB	SUBCONTRACTOR
G	GAS		SUBFLOOR
GA	GAUGE		SHEAR WALL
	GALVANIZED	SYM	
GC	GENERAL CONTRACTOR	Т	TILE, TREAD, TOP, OR
	GARBAGE DISPOSAL	'	TRANSFORMER
GL	GLASS	T & G	
GR	GRADE	TBD	
GYP BD	GYPSUM BOARD	TEL	TELEPHONE
HC	HANDICAP	THK	THICK
HDR		ТО	
HDWD		TOC	
HT		TOP	
	HORIZONTAL	TOS	
HR	HOUR	TOW	
INSUL	INSULATION	TP	
INT	INTERIOR	TV TYP	
JT	JOINT OR JOINT TRENCH		_
J i		UNO	UNLESS NOTED OTHERWISE
	LINEN CLOSET	VERT	VERTICAL
	LAMINATE		
LAM	LAVATORY	W W/	WEST, WASHER, OR WATER
LAM LAV	LIGHT	W/	WITH
LAM LAV		WC	WATER CLOSET WOOD
LAM LAV LT MAX	MAXIMUM	\ \/\/ I \	V V U U U U
LAM LAV LT MAX MECH	MAXIMUM MECHANICAL	WD	WATER HEATER
LAM LAV LT MAX MECH MFR	MAXIMUM MECHANICAL MANUFACTURER	WH	
LAM LAV LT MAX MECH MFR MH	MAXIMUM MECHANICAL MANUFACTURER MANHOLE	WH W×H	WIDTH BY HEIGHT
LAM LAV LT MAX MECH MFR MH MIN	MAXIMUM MECHANICAL MANUFACTURER MANHOLE MINIMUM	WH W x H WNDW	WIDTH BY HEIGHT WINDOW
LAM LAV LT MAX MECH MFR MH MIN MISC	MAXIMUM MECHANICAL MANUFACTURER MANHOLE MINIMUM MISCELLANEOUS	WH W x H WNDW W/O	WIDTH BY HEIGHT WINDOW WITHOUT
LAM LAV LT MAX MECH MFR MH MIN MISC MLDG	MAXIMUM MECHANICAL MANUFACTURER MANHOLE MINIMUM MISCELLANEOUS MOULDING	WH W x H WNDW W/O	WIDTH BY HEIGHT WINDOW WITHOUT WATERPROOF
LAM LAV LT MAX MECH MFR MH MIN	MAXIMUM MECHANICAL MANUFACTURER MANHOLE MINIMUM MISCELLANEOUS	WH W x H WNDW W/O WP	WIDTH BY HEIGHT WINDOW WITHOUT WATERPROOF

PROJECT SCOPE

NEW 2-STORY, SINGLE-FAMILY HOME WITH ATTACHED 2 CAR GARAGE ON VACANT PARCEL

PLANNING DATA

PROJECT COMMON ADDRESS: TBD 10TH STREET MONTARA, CA 94037

ASSESSOR'S PARCEL NUMBER: 036-031-100 R-1 / S-17 / CZ / DR

BEARING AND NON-BEARI WALLS (LESS THAN 5' FRO	DM
PROPERTY LINE):	1-HOUR
OPENINGS NOT PERMITTE FROM PROPERTY LINE	ED LESS THAN 3'
NUMBER OF STORIES:	2
ALL WORK TO CONFORM CFC, CPC, CMC, CEC, CEn	

BUILDING CODE DATA

	PROJECT DIRECTOR	RY	
SERVICE	COMPANY	CONTACT	TELEPHONE
APPLICANT / OWNER	-	TIMOTHY & JACQUELINE WALLEY	
DESIGN / DRAFTING	BRIAN BRINKMAN DRAFTING & DESIGN INC.	BRIAN BRINKMAN	(650) 922-799
SURVEYOR	SAVIOR P. MICALLEF LAND SURVEYING	SAVIOR MICALLEF	(805) 709-242
GEOTECHNICAL ENGINEER	SIGMA PRIME GEOSCIENCES	CHARLES KISSICK	(650) 728-359
CIVIL ENGINEER	SIGMA PRIME GEOSCIENCES	CHARLES KISSICK	(650) 728-359
LANDSCAPE DESIGN	FLORA FARM	JERRY WHITING	(650) 726-922

PROJECT NOTES

FIRE SPRINKLERS REQUIRED, UNDER A SEPARATE PERMIT, PER NFPA 13D STANDARDS.

CALGREEN CONSTRUCTION REQUIREMENTS

- CONTRACTOR SHALL PROVIDE, AT THE TIME OF FINAL INSPECTION, AN OPERATION AND MAINTENANCE MANUAL TO THE OWNER OR OCCUPANT. ADDRESSING ITEMS 1 THROUGH 10 IN CALGREEN SECTION 4.410.1.
- * PER CALGREEN SECTION 4.408.2, CONTRACTOR SHALL PROVIDE AND SUBMIT A CONSTRUCTION WASTE MANAGEMENT PLAN, DIVERTING A
- MINIMUM OF 65% OF WASTE GENERATED AT THE SITE TO RECYCLE OR SALVAGE, TO THE BUILDING DEPARTMENT. THE FOLLOWING INFORMATION
- SHALL BE PROVIDED IN THE PLAN:
- · IDENTIFY MATERIALS TO BE RECYCLED, REUSED, OR SALVAGED
- SPECIFY IF MATERIALS WILL BE SORTED ON SITE OR MIXED FOR TRANSPORTATION
- IDENTIFY THE DIVERSION FACILITY(IES) TO BE USED
- IDENTIFY CONSTRUCTION METHODS TO BE USED TO LIMIT WASTE GENERATION SPECIFY THAT THE AMOUNT OF MATERIALS DIVERTED ARE TO BE CALCULATED BY WEIGHT OR VOLUME * AUTOMATIC IRRIGATION SYSTEMS CONTROLLERS INSTALLED AT THE TIME OF FINAL INSPECTION
- SHALL BE WEATHER-BASED. * PROTECT ANNULAR SPACES AROUND PIPES, ELECTRIC CABLES, AND CONDUITS AT EXTERIOR WALLS AGAINST THE PASSAGE OF RODENTS.
- * COVER DUCT OPENINGS AND OTHER RELATED AIR DISTRIBUTION COMPONENT OPENINGS DURING
- CONSTRUCTION.
- * ADHESIVES, SEALANTS, AND CAULKS SHALL BE COMPLIANT WITH VOC AND OTHER TOXIC COMPOUND LIMITS.
- * PAINTS, STAINS, AND OTHER COATINGS SHALL BE COMPLIANT WITH VOC LIMITS. AEROSOL PAINTS AND COATINGS SHALL BE COMPLIANT WITH PRODUCT WEIGHTED MIR LIMITS FOR
- ROC AND OTHER TOXIC COMPOUNDS.
- VERIFICATION OF COMPLIANCE SHALL BE PROVIDED.
- * CARPET AND CARPET SYSTEMS SHALL BE COMPLIANT WITH VOC LIMITS. * MINIMUM OF 80% OF FLOOR AREA RECEIVING RESILIENT FLOORING SHALL COMPLY WITH SECTION
- 4.504.4. * PARTICLEBOARD, MEDIUM DENSITY FIBERBOARD, AND HARDWOOD PLYWOOD USED IN INTERIOR
- FINISH SYSTEMS SHALL COMPLY WITH LOW
- FORMALDEHYDE EMISSION STANDARDS. * INSTALL CAPILLARY BREAK AND VAPOR RETARDER AT SLAB ON GRADE FOUNDATIONS.
- * CHECK MOISTURE CONTENT OF BUILDING MATERIALS USED IN WALL AND FLOOR FRAMING BEFORE
- * EACH BATHROOM SHALL BE MECHANICALLY VENTILATED WITH AN ENERGY STAR EXHAUST FAN. AND FAN MUST BE CONTROLLED BY A HUMIDITY
- * DUCT SYSTEMS SHALL BE SIZED, DESIGNED, AND EQUIPMENT SELECTED PER SECTION 4.507.2. HVAC SYSTEM INSTALLERS MUST BE TRAINED
- AND CERTIFIED AND SPECIAL INSPECTORS EMPLOYED BY THE ENFORCING AGENCY MUST BE QUALIFIED.

PROJECT II	NFORMATION
LOT SIZE	6,000 SF
(N) LEVEL 1 LIVING AREA	1,340 SF (CONDITIONED)
(N) LEVEL 2 LIVING AREA	981 SF (CONDITIONED)
(N) LOFT LIVING AREA	285 SF (CONDITIONED)
(N) TOTAL LIVING AREA	1,340 SF + 981 SF + 285 SF = 2,095 SF
(N) GARAGE AREA	442 SF (UN-CONDITIONED)
(N) COVERED FRONT PORCH	132 SF (UN-CONDITIONED)
(N) TOTAL FLOOR AREA	3,179 SF (CONDITIONED)
(N) F.A.R.	1,340 + 981 + 285 + 442 + 132 = 3,180 / 6,000 = 53.00% (53% MAX)
(N) REAR DECK AREA (UNCOVERED)	222 SF (UN-CONDITIONED)
(N) LEVEL 2 ROOF DECK (UNCOVERED)	198 SF (UN-CONDITIONED)
(N) LOT COVERAGE	1,340 + 442 + 132 + 180 = 2,094 SF 2,094 SF / 6,000 SF = 34.90%

TITLE SHEET
PROPOSED PERSPECTIVES
MATERIALS PERSPECTIVE
ORIGINAL TOPOGRAPHIC SURVEY
SITE PLAN
GRADING DRAINAGE PLAN
EROSION CONTROL PLAN
LANDSCAPE PLAN
NEW LEVEL 1 FLOOR PLAN
NEW LEVEL 2 FLOOR PLAN
NEW ROOF PLAN
FLOOR AREA DIAGRAMS
NEW FRONT AND RIGHT ELEVATIONS
NEW REAR AND LEFT ELEVATIONS
CROSS SECTIONS

	DRAWING INDEX
A0.0	TITLE SHEET
A0.1	PROPOSED PERSPECTIVES
A0.2	MATERIALS PERSPECTIVE
1 of 1	ORIGINAL TOPOGRAPHIC SURVEY
A1.1	SITE PLAN
C-1	GRADING DRAINAGE PLAN
C-2	EROSION CONTROL PLAN
L-1	LANDSCAPE PLAN
A2.1	NEW LEVEL 1 FLOOR PLAN
A2.2	NEW LEVEL 2 FLOOR PLAN
A2.3	NEW ROOF PLAN
A2.4	FLOOR AREA DIAGRAMS
A3.1	NEW FRONT AND RIGHT ELEVATIONS
A3.2	NEW REAR AND LEFT ELEVATIONS
A3.3	CROSS SECTIONS

V	/ICINITY M	AP
Main St 10th 28t	A state of the sta	A A B A B A B A B A B A B A B A B A B A
Ave Samilone Ave		All About ME Retreats Oth Street
Taplone Ave	This se	
13th St	12th St	SUBJECT PARCEL
13th s.		




DESCRIPTION	2ND DESIGN	3RD DESIGN	DESIGN SET	PLANNING SUBMITTAL	PLANNING RESUBMITTAL
DATE	09/12/2019	10/07/2019	11/06/2019	01/28/2020	03/25/2020
REV	2	3	4	5	9
			Vac		


SHEET TITLE

TITLE SHEET




1 3D View 3









ON OF NEW 2-STORY Y HOME WITH ARAGE ON VACANT

SHEET TITLE

PROPOSED PERSPECTIVES

SHEET

A0.1



1 MATERIALS PERSPECTIVE


EXTERIOR MATERIALS:


- 1. <u>SIDING 1</u>: HARDIEPLANK LAP SIDING WITH 7" REVEAL PAINTED BENJAMIN MOORE 1591 'STERLING'
- 2. <u>SIDING 2</u>: HARDIEPANEL SIDING WITH HARDIE TRIM PAINTED BENJAMIN MOORE 1591 'STERLING'
- 3. <u>TRIM</u>: REDWOOD FASCIA BOARD AND EXTERIOR TRIM PAINTED BENJAMIN MOORE 2143-70 'SIMPLY WHITE'
- 4. <u>WINDOWS</u>: WHITE MILGARD VINYL WINDOWS
- 5. FRONT DOOR: WOOD DOOR PAINTED BENJAMIN MOORE 2143-70 'SIMPLY WHITE'
- 6. <u>ROOFING</u>: OWENS CORNING OAKRIDGE COMPOSITION ASPHALT ROOFING SHINGLES IN 'TWILIGHT BLACK' COLOR
- 7. <u>GUTTERS</u>: GALVANIZED GUTTERS AND DOWNSPOUTS PAINTED BENJAMIN MOORE 2173-10 'EARTHLY RUSSET'
- 8. <u>FENCING</u>: REDWOOD GOOD NEIGHBOR FENCE
- 9. <u>STONE VENEER</u>: ELDORADO STONE'S STACKED STONE EUROPEAN LEDGE IN 'GLACIER' COLOR
- 10. <u>RAILING</u>: STAINLESS STEEL CABLE RAILING WITH BLACK METAL POSTS AND WOOD CAP

2 E 4 R	09/12/2019 2ND DESIGN 10/07/2019 3RD DESIGN 11/06/2019 DESIGN SET 01/28/2020 PLANNING SUBMITTAL BRIAN BRINKMAN DRAFTING & DESIGN, INC. 1690 Francisco Blvd. Pacifica, CA 94044
$\overline{}$	03/25/2020 PLANNING RESUBMITTAL (650) 922-7993

MATERIALS

PERSPECTIVE





SITE PLAN LINE LEGEND

—— — — ELECTRICAL

- - SANITARY SEWER **●** • • • **●** GAS STRAW WATTLE

> 2 0 8 4 5 9 ST SCOPE: TRUCTION OF NEW 2-STORY E FAMILY HOME WITH HED GARAGE ON VACANT

PROJECT NAME:


NEW SINGLE FAMILY HOM
RUSSELL RESIDENCE

SHEET TITLE

SITE PLAN

SHEET

A1.1



LEGEND

// EXISTING CONTOURS PROPOSED CONTOURS PROPOSED SPOT ELEVATION

4" MIN SOLID DRAIN PIPE

— 4" MIN PERFORATED DRAIN PIPE

GENERAL NOTES

- 1. PLANS PREPARED AT THE REQUEST OF:
- FRANK WALLEY, OWNER
- 2. TOPOGRAPHY BY SAVIOR MICALLEF, SURVEYED JUNE, 2019. 3. THIS IS NOT A BOUNDARY SURVEY.
- 4. ELEVATION DATUM ASSUMED
- 5. STORMWATER MANAGEMENT CONSTRUCTION INSPECTIONS SHALL BE SCHEDULED FOR APPLICABLE DRAINAGE INSPECTIONS, WHICH INCLUDE SITE CLEARANCE AND EROSION CONTROL MEASURES INSTALLATION AS WELL AS INSPECTION OF MAJOR DRAINAGE CONTAINMENT, TREATMENT, AND CONVEYANCE DEVICES BEFORE BEING BURIED (INCLUDING REQUIRED MATERIAL LABELS, E.G. PIPES, SUG-BGRADE MATERIALS, ETC.). PLEASE FOLLOW THE INSPECTION CARD INSTRUCTIONS AND PHONE NUMBER (650-306-8405 EXT 181) TO SCHEDULE COUNTY DRAINAGE INSPECTIONS ACCORDINGLY. THERE SHALL BE THREE INSPECTIONS: ONE FOR EROSION CONTROL INSTALLATION, ONE BEFORE DRAINAGE FACILITIES ARE BURIED, AND ONE FOR FINAL WALK AROUND.

DRAINAGE NOTES

- 1. DRAINAGE INTENT: IT IS THE INTENT OF THE DRAINAGE SYSTEM TO CONVEY ROOF AND DRIVEWAY RUNOFF TO A SAFE LOCATION, AND TO MINIMIZE EXCESSIVE MOISTURE AROUND FOUNDATIONS. DIRECT SLOPES SUCH THAT STORMWATER WILL NOT BE DIVERTED ONTO ADJACENT PROPERTIES.
- 2. ALL DOWNSPOUT DRAIN LINES AND THE DRIVEWAY TRENCH DRAIN SHALL LEAD TO DETENTION BASIN, AS SHOWN. THE DETENTION BASIN SHALL OVERFLOW INOT THE ADJACENT LANDSCPAING AREA.
- 3. ALL ROOF DRAINAGE PIPES SHALL BE 4" DIAMETER MINIMUM SOLID PIPE, SLOPED AT 1% MINIMUM.
- 4. IT IS THE PROPERTY OWNER'S RESPONSIBILITY TO CHECK ON ALL STORMWATER FACILITIES SUCH AS ROOF GUTTERS, DOWNSPOUT LINES, AND THE DETENTION BASIN/ENERGY DISSIPATER TO BE SURE THAT THEY ARE CLEAR OF EXCESSIVE DEBRIS AND OPERATING EFFICIENTLY. THE FACILITIES SHALL BE CHECKED EVERY FALL AND PERIODICALLY DURING THE RAINY SEASON.

GRADING NOTES

CUT VOLUME: 235 CY FILL VOLUME: 75 CY TOTAL: 310 CY


VOLUMES ABOVE ARE APPROXIMATE.

THE SUBGRADE BELOW ALL PAVED AREAS SHALL BE BASEROCK COMPACTED TO 95%.


ALL GRADING SHALL CONFORM TO LOCAL CODES AND ORDINANCES.

ALL TRENCHES UNDER PROPOSED PAVED AREAS OR CONCRETE SHALL BE BACKFILLED TO SUBGRADE ELEVATION WITH COMPACTED APPROVED GRANULAR MATERIALS. IF TRENCHES ARE IN PROPOSED LANDSCAPE AREAS, THEY SHALL BE BACKFILLED WITH COMPACTED APPROVED GRANULAR MATERIAL TO WITHIN ONE FOOT OF FINISHED GRADE, AND THEN FILLED WITH HAND TAMPED SOILS.


SECTION AND DETAIL CONVENTION







SHEE



3/4" CLEAN DRAIN ROCK, WRAPPED IN FILTER FABRIC


4" DIAM. PERF. PIPE

2 WALL DRAIN CICI NOT TO SCALE NOTE: CONCEPTUAL DRAWING: REFER TO BUILDING PLANS FOR

ACTUAL DETAIL.




GENERAL EROSION AND SEDIMENT CONTROL NOTES



- There will be no stockpiling of soil. All excavated soil will be hauled off-site as it is excavated.
- Perform clearing and earth-moving activities only during dry weather. Measures to ensure adequate erosion and sediment control shall be installed prior to earth-moving activities and construction.
- · Erosion control materials to be on-site during off-season.
- Measures to ensure adequate erosion and sediment control are required year-round.
 Stabilize all denuded areas and maintain erosion control measures continuously between October 1 and April 30.
- Store, handle, and dispose of construction materials and wastes properly, so as to prevent their contact with stormwater.
- Control and prevent the discharge of all potential pollutants, including pavement cutting wastes, paints, concrete, petroleum products, chemicals, wash water or sediments, and non-stormwater discharges to storm drains and watercourses.
- Avoid cleaning, fueling, or maintaining vehicles on-site, except in a designated area where wash water is contained and treated.
- · Limit and time applications of pesticides and fertilizers to prevent polluted runoff.
- · Limit construction access routes to stabilized, designated access points
- Avoid tracking dirt or other materials off-site; clean off-site paved areas and sidewalks using dry sweeping methods.
- Train and provide instruction to all employees and subcontractors regarding the Watershed Protection Maintenance Standards and construction Best Management Practices.
- · Placement of erosion materials is required on weekends and during rain events.
- The areas delineated on the plans for parking, grubbing, storage etc., shall not be enlarged or "run over."
- Dust control is required year-round.
- Erosion control materials shall be stored on-site.
- There are no trees or driplines oin the site.

EROSION CONTROL POINT OF CONTACT

THIS PERSON WILL BE RESPONSIBLE FOR EROSION CONTROL AT THE SITE AND WILL BE THE COUNTY'S MAIN POINT OF CONTACT IF CORRECTIONS ARE REQUIRED.






Sigma Prime Geosciences.
SIGMA PRIME GEOSCIENCES, INC. 332 PRINCETON AVENUE HALF MOON BAY, CA 94019 (650) 728-3590 FAX 728-3593

STABILIZED CONSTRUCTION ENTRANCE/EXIT TC-1 Crushed aggregate Filter fabric

12" Min, unless otherwise specified by a soils engineer



PLAN NTS

Existing

Grade

EROSION AND SEDIMEN
CONTROL PLAN
WALLEY PROPERTY

10' min, or as required to accomodate anticipated traffic, whichever

SHEET

C-2

Vertical spacing measured along the face of the slope varies between 10° and 20° Install a fiber roll near slope where it transitions into a steeper slope

TYPICAL FIBER ROLL INSTALLATION

N.T.S.

Fiber roll
8" min

3/4" × 3/4" wood stokes max 4" spacing

ENTRENCHMENT DETAIL N.T.S.

If more than one fiber roll is placed in a row, the rolls must be overlapped, not abutted. Turn the ends of the fiber roll up-slope to prevent runoff from going around the roll.

CONCRETE WASTE MANAGEMENT

1/1 1 1 1 1 1

10 MIL PLAN
PLASTIC LINING PLAN
NOT TO SCALE
TYPE "ABOVE GRADE"
WITH STRAW BALES

FIBER ROLLS

8-MW

STAPLE DETAIL

1. ACTUAL LAYOUT DETERMINED IN FIELD.

2. THE CONCRETE WASHOUT SIGN SHALL BE INSTALLED WITHIN 30 FT. OF THE TEMPORARY CONCRETE WASHOUT FACILITY.

SE-5




Construction Best Management Practices (BMPs)

Construction projects are required to implement the stormwater best management practices (BMP) on this page, as they apply to your project, all year long.

Clean Water. Healthy Community.

Materials & Waste Management



Non-Hazardous Materials

- ☐ Berm and cover stockpiles of sand, dirt or other construction material with tarps when rain is forecast or if not actively being used within 14 days.
- ☐ Use (but don't overuse) reclaimed water for dust control.

Hazardous Materials

- ☐ Label all hazardous materials and hazardous wastes (such as pesticides, paints, thinners, solvents, fuel, oil, and antifreeze) in accordance with city, county, state and federal regulations.
- ☐ Store hazardous materials and wastes in water tight containers, store in appropriate secondary containment, and cover them at the end of every work day or during wet weather or when rain is forecast.
- ☐ Follow manufacturer's application instructions for hazardous materials and be careful not to use more than necessary. Do not apply chemicals outdoors when rain is forecast within 24 hours.
- Arrange for appropriate disposal of all hazardous wastes.

Waste Managemen

- X Cover waste disposal containers securely with tarps at the end of every work day and during wet weather.
- Check waste disposal containers frequently for leaks and to make sure they are not overfilled. Never hose down a dumpster on the construction site.
- (Clean or replace portable toilets, and inspect them frequently for leaks and spills.
- Dispose of all wastes and debris properly. Recycle materials and wastes that can be recycled (such as asphalt, concrete, aggregate base materials, wood, gyp board, pipe, etc.)
- ☑ Dispose of liquid residues from paints, thinners, solvents, glues, and cleaning fluids as hazardous waste.

Construction Entrances and Perimeter

- ▲ Establish and maintain effective perimeter controls and stabilize all construction entrances and exits to sufficiently control erosion and sediment discharges from site and tracking off site.
- ▼ Sweep or vacuum any street tracking immediately and secure sediment source to prevent further tracking. Never hose down streets to clean up tracking.

Equipment Management & Spill Control



Maintenance and Parking


- Designate an area, fitted with appropriate BMPs, for vehicle and equipment parking and storage.
- ☐ Perform major maintenance, repair jobs, and vehicle and equipment washing off site.
- ☐ If refueling or vehicle maintenance must be done onsite, work in a bermed area away from storm drains and over a drip pan or drop cloths big enough to collect fluids. Recycle or dispose of fluids as hazardous waste.
- ☐ If vehicle or equipment cleaning must be done onsite, clean with water only in a bermed area that will not allow rinse water to run into gutters, streets, storm drains, or surface waters.
- ☐ Do not clean vehicle or equipment onsite using soaps, solvents, degreasers, or steam cleaning equipment.

Spill Prevention and Control

- Keep spill cleanup materials (e.g., rags, absorbents and cat litter) available at the construction site at all times.
- ☐ Inspect vehicles and equipment frequently for and repair leaks promptly. Use drip pans to catch leaks until repairs are made.
- (Clean up spills or leaks immediately and dispose of cleanup materials properly.
- Do not hose down surfaces where fluids have spilled.

 Use dry cleanup methods (absorbent materials, cat litter, and/or rags).
- Sweep up spilled dry materials immediately. Do not try to wash them away with water, or bury them.
- ☐ Clean up spills on dirt areas by digging up and properly disposing of contaminated soil.
- □ Report significant spills immediately. You are required by law to report all significant releases of hazardous materials, including oil. To report a spill: 1) Dial 911 or your local emergency response number, 2) Call the Governor's Office of Emergency Services Warning Center, (800) 852-7550 (24 hours).

Earthmoving



- Schedule grading and excavation work during dry weather.
- ▼ Stabilize all denuded areas, install and maintain temporary erosion controls (such as erosion control fabric or bonded fiber matrix) until vegetation is established.
- Remove existing vegetation only when absolutely necessary, and seed or plant vegetation for erosion control on slopes or where construction is not immediately planned.
- Prevent sediment from migrating offsite and protect storm drain inlets, gutters, ditches, and drainage courses by installing and maintaining appropriate BMPs, such as fiber rolls, silt fences, sediment basins, gravel bags, berms, etc.
- ☐ Keep excavated soil on site and transfer it to dump trucks on site, not in the streets.

Contaminated Soils

- ☐ If any of the following conditions are observed, test for contamination and contact the Regional Water Quality Control Board:
- Unusual soil conditions, discoloration, or odor.
- Abandoned underground tanks.
- Abandoned wells
- Buried barrels, debris, or trash

Paving/Asphalt Work



- Avoid paving and seal coating in wet weather or when rain is forecast, to prevent materials that have not cured from contacting stormwater runoff.
- Cover storm drain inlets and manholes when applying seal coat, tack coat, slurry seal, fog seal, etc.
- Collect and recycle or appropriately dispose of excess abrasive gravel or sand. Do NOT sweep or wash it into gutters.
- Do not use water to wash down fresh asphalt concrete pavement.

Sawcutting & Asphalt/Concrete Removal


- ☐ Protect nearby storm drain inlets when saw cutting. Use filter fabric, catch basin inlet filters, or gravel bags to keep slurry out of the storm drain system.
- ☐ Shovel, abosorb, or vacuum saw-cut slurry and dispose of all waste as soon as you are finished in one location or at the end of each work day (whichever is sooner!).
- ☐ If sawcut slurry enters a catch basin, clean it up immediately.

Concrete, Grout & Mortar Application




- ☐ Store concrete, grout, and mortar away from storm drains or waterways, and on pallets under cover to protect them from rain, runoff, and wind.
- Wash out concrete equipment/trucks offsite or in a designated washout area, where the water will flow into a temporary waste pit, and in a manner that will prevent leaching into the underlying soil or onto surrounding areas. Let concrete harden and dispose of as garbage.
- ☐ When washing exposed aggregate, prevent washwater from entering storm drains. Block any inlets and vacuum gutters, hose washwater onto dirt areas, or drain onto a bermed surface to be pumped and disposed of properly.

Landscaping



- Protect stockpiled landscaping materials from wind and rain by storing them under tarps all year-round.
- ☐ Stack bagged material on pallets and under cover.
- Discontinue application of any erodible landscape material within 2 days before a forecast rain event or during wet weather.

Painting & Paint Removal



Painting Cleanup and Removal

- Never clean brushes or rinse paint containers into a street, gutter, storm drain, or stream.
- ▼ For water-based paints, paint out brushes to the extent possible, and rinse into a drain that goes to the sanitary sewer.

 Never pour paint down a storm drain.
- ☐ For oil-based paints, paint out brushes to the extent possible and clean with thinner or solvent in a proper container. Filter and reuse thinners and solvents. Dispose of excess liquids as hazardous waste.
- Paint chips and dust from non-hazardous dry stripping and sand blasting may be swept up or collected in plastic drop cloths and disposed of as trash.
- ☐ Chemical paint stripping residue and chips and dust from marine paints or paints containing lead, mercury, or tributyltin must be disposed of as hazardous waste.


 Lead based paint removal requires a statecertified contractor.

Dewatering



- ☐ Discharges of groundwater or captured runoff from dewatering operations must be properly managed and disposed. When possible send dewatering discharge to landscaped area or sanitary sewer. If discharging to the sanitary sewer call your local wastewater treatment plant.
- ☐ Divert run-on water from offsite away from all disturbed areas.
- ☐ When dewatering, notify and obtain approval from the local municipality before discharging water to a street gutter or storm drain. Filtration or diversion through a basin, tank, or sediment trap may be required.
- ☐ In areas of known or suspected contamination, call your local agency to determine whether the ground water must be tested. Pumped groundwater may need to be collected and hauled off-site for treatment and proper disposal.

Storm drain polluters may be liable for fines of up to \$10,000 per day!



PLANTILIST	COMMON NAME	017/5,22	WI	TYPE
melaleuch incha	Gay Howay myiztle	4 - 50x(L	SHEUB
CIANOTING RAY HART MAN			4	SHRUB
AZARA MICROPHYLLA	BOYLEST AZARA	4 - Tyse	M	541WB
ARBUTIS UNEDO	STRAWBERRY THE		۷	TREE
GRAVILLEL CONFERD			L	s4rus
GARRYA Elliptica	COAST SILK TASSG		L	Trek
HAKEA SUAVEOLENS		3-5 get	۷	SHRUB
Solly A HETEROPHYL			_ L	GR. COVER
Rosmaniaus OFF.c. NA		•	L	GR COVER
RUBUS CALYCINDIDES			M	GR. COUEL
WRSTRINGIS FRUTICOS			۷	SHRUB
MALALEUCK LINANIFOL.	A FLACLER PAPERS	mk 3-1541	L	SHRUB/TREE

TOTAL PLANTS 7-15gel 15-5gel 41-1gel

SPIDER Flower 4- Igal

1, INCORPORATE COMPOSTAT A RATIE OF AT COST HW. YAS FEEL 1000 21 TO A DEGTE

BE APPLIED ON ALL BY POSED SO. (SURFACES OF PLANTING AREAS, BLOEFT IN A TEAS OF

MOTE (WATER EFFICIENT LANDSCAPE OF DINAME (MWE 6) SHORT FORM PRESCRIPTION COMPLIANCE

X THIS PROJECT DORS INCORPORATE LANDSCHPING EQUIL TO OR LESS THAN 2,500 St. AND WILL BE USING THIS FORM TO INDENTIFY PRESCRIPTION REQUIREMENTS WHICH WILL BE INCLUSED AS FANT OF THE LINSCHEE

> I CERT. FY THE ABOVE IS CORRECT AND ACTURE to comply with THE REQUIREMENTS

I AGREE TO COMPLY WITH THE REQUIREMENTS OF THE PRESCIPTIVE COMPLIANCE OFT, OF THE MUCLU DER AFFENDIX D.

North

ı	PLANNING RESUBMITTAL	03/25/2020	9
	PLANNING SUBMITTAL	01/28/2020	2
	DESIGN SET	11/06/2019	4
	3RD DESIGN	10/02/2019	3
	2ND DESIGN	09/12/2019	2

. ON OF NEW 2-STORY Y HOME WITH RAGE ON VACANT

PROJECT NAME:

NEW SINGLE FAMILY HOME
RUSSELL RESIDENCE

SHEET TITLE

LANDSCAPE PLAN

SHEET

L-1

NEW PLUMBING FIXTURE NOTES:

- **MAX FLOW RATE OF SHOWERHEADS SHALL BE 1.8 GPM**
- MAX FLOW RATE OF LAVATORY FAUCETS SHALL BE 1.2 GPM MAX FLOW RATE OF KITCHEN FAUCETS SHALL BE 1.8 GPM

" ALL TOILETS SHALL BE MAX 1.28 GPF **EGRESS NOTES:**

AT LEAST ONE WINDOW IN EACH BEDROOM SHALL MEET THE FOLLOWING REQUIREMENTS:

- **MIN. 5.7 SF IN OVERALL SIZE**
- MIN. 24" CLEAR OPENING HEIGHT
- MIN. 20" CLEAR OPENING WIDTH " SILL A MAX. OF 44" ABOVE FINISHED FLOOR


GENERAL NOTES:

ALL FRAMING DIMENSIONS ARE TO ROUGH FRAMING UNLESS OTHERWISE NOTED.

						_			
				Sill	Head				Phase
Mark	Level	Width	Height	Height	Height	Operation	Comments	Phase Created	Demolished
1	LEVEL 1 F.F.	3' - 0"	5' - 0"	3' - 0"	8' - 0"	SINGLE HUNG		New Construction	None
2	LEVEL 1 F.F.	3' - 0"	5' - 0"	3' - 0"	8' - 0"	SINGLE HUNG		New Construction	None
- 3	LEVEL 1 F.F.	3' - 0"	5' - 0"	3' - 0"	8' - 0"	SINGLE HUNG		New Construction	None
4	LEVEL 1 F.F.	3' - 0"	5' - 0"	3' - 0"	8' - 0"	SINGLE HUNG		New Construction	None
5	LEVEL 1 F.F.	3' - 6"	7' - 0"	1' - 0"	8' - 0"	FIXED		New Construction	None
6	LEVEL 1 F.F.	3' - 6"	7' - 0"	1' - 0"	8' - 0"	FIXED		New Construction	None
7	LEVEL 1 F.F.	3' - 6"	7' - 0"	1' - 0"	8' - 0"	FIXED		New Construction	None
8	LEVEL 1 F.F.	4' - 0"	4' - 0"	4' - 0"	8' - 0"	FIXED		New Construction	None
9	LEVEL 1 F.F.	2' - 6"	4' - 0"	4' - 0"	8' - 0"	CASEMENT		New Construction	None
10	LEVEL 1 F.F.	3' - 6"	7' - 0"	1' - 0"	8' - 0"	FIXED		New Construction	None
11	LEVEL 1 F.F.	2' - 6"	4' - 0"	4' - 0"	8' - 0"	FIXED		New Construction	None
12	LEVEL 1 F.F.	3' - 6"	7' - 0"	1' - 0"	8' - 0"	FIXED		New Construction	None
13	LEVEL 1 F.F.	3' - 6"	7' - 0"	1' - 0"	8' - 0"	FIXED		New Construction	None
14	LEVEL 1 F.F.	2' - 6"	4' - 0"	4' - 0"	8' - 0"	CASEMENT		New Construction	None
19	LEVEL 1 F.F.	2' - 6"	4' - 0"	4' - 0"	8' - 0"	FIXED		New Construction	None

LEVEL 1 LIVING AREA = 1,340 SF

			L	EVEL 1	DOOR SCHE	DULE		
Mark	Level	Count	Width	Height	Operation	Comments	Phase Created	Phase Demolished
D1	LEVEL 1 F.F.	1	3' - 0"	8' - 0"	SINGLE		New Construction	None
D2	LEVEL 1 F.F.	1	6' - 0"	8' - 0"	DOUBLE		New Construction	None
D3	LEVEL 1 F.F.	1	2' - 8"	6' - 8"	SINGLE		New Construction	None
D4	LEVEL 1 F.F.	1	2' - 8"	6' - 8"	POCKET		New Construction	None
D5	LEVEL 1 F.F.	1	2' - 8"	6' - 8"	SINGLE		New Construction	None
D6	LEVEL 1 F.F.	1	12' - 0"	8' - 0"	SLIDING		New Construction	None
D7	LEVEL 1 F.F.	1	2' - 4"	0' - 0"	SLIDING		New Construction	None
D8	LEVEL 1 F.F.	1	5' - 0"	6' - 8"	SINGLE		New Construction	None
D9	LEVEL 1 F.F.	1	2' - 6"	6' - 8"	POCKET		New Construction	None
D10	LEVEL 1 F.F.	1	2' - 2"	6' - 6"	SINGLE		New Construction	None
D11	LEVEL 1 F.F.	1	2' - 6"	6' - 8"	SINGLE		New Construction	None
D12	GARAGE F.F.	1	15' - 0"	8' - 0"	OVERHEAD		New Construction	None
D13	GARAGE F.F.	1	3' - 0"	6' - 8"	SINGLE		New Construction	None
D14	GARAGE F.F.	1	2' - 2"	6' - 6"	SINGLE		New Construction	None



44' - 0"

18' - 0"

16' - 1 1/2"



9' - 10 1/2"

PROPOSED STUD WALL PROPOSED PARTIAL HEIGHT WALL EXISTING / PROPOSED CONCRETE WALL EXISTING WALL TO REMAIN

□ □ □ □ WALL TO BE DEMOLISHED

DESCRIPTION	2ND DESIGN	3RD DESIGN	DESIGN SET	PLANNING SUBMITTAL	PLANNING RESUBMITTAL
DATE	09/12/2019	10/07/2019	11/06/2019	01/28/2020	03/25/2020
REV	2	က	4	5	9

N OF NEW 2-STORY Y HOME WITH RAGE ON VACANT

PROJECT NAME:

NEW SINGLE FAMILY HOME
RUSSELL RESIDENCE

SHEET TITLE

NEW LEVEL 1 FLOOR PLAN

SHEET

A2.1

NEW PLUMBING FIXTURE NOTES:

- MAX FLOW RATE OF SHOWERHEADS SHALL BE 1.8 GPM
- MAX FLOW RATE OF LAVATORY FAUCETS SHALL BE 1.2 GPM
- MAX FLOW RATE OF KITCHEN FAUCETS SHALL BE 1.8 GPM **ALL TOILETS SHALL BE MAX 1.28 GPF**
- EGRESS NOTES:

AT LEAST ONE WINDOW IN EACH BEDROOM SHALL MEET THE **FOLLOWING REQUIREMENTS:**

- MIN. 5.7 SF IN OVERALL SIZE
- MIN. 24" CLEAR OPENING HEIGHT
- MIN. 20" CLEAR OPENING WIDTH
- SILL A MAX. OF 44" ABOVE FINISHED FLOOR

Level

LOFT F.F.

LOFT F.F.

LOFT F.F.

LOFT F.F.

LEVEL 2 F.F.

D15 LEVEL 2 F.F.

D16 LEVEL 2 F.F.

D17 LEVEL 2 F.F.

D18 LEVEL 2 F.F.

D19 LEVEL 2 F.F.

D20 LEVEL 2 F.F.

D21 LEVEL 2 F.F.

D23 LEVEL 2 F.F.

D24 LEVEL 2 F.F.

D25 LEVEL 2 F.F.

D26 LOFT F.F.

D27 LOFT F.F.

D28 LOFT F.F.

D29 LOFT F.F.

D30 LEVEL 2 F.F.

GENERAL NOTES:

Mark

22

23

ALL FRAMING DIMENSIONS ARE TO ROUGH FRAMING UNLESS OTHERWISE NOTED.

LEVEL 2 WINDOW SCHEDULE

Operation

Comments

New Construction | None

Phase

Phase Created Demolished

New Construction None

New Construction

Head

Sill

| 2' - 6" | 2' - 6" | 5' - 6" | 8' - 0" | AWNING

| 3' - 0" | 3' - 6" | 0' - 2" | 3' - 8" | FIXED

|3' - 0" | 4' - 0" | 4' - 0" | 8' - 0" | FIXED

|3' - 0" | 4' - 0" | 4' - 0" | 8' - 0" | FIXED

| 3' - 0" | 2' - 6" | 5' - 6" | 8' - 0" | AWNING

|3' - 0" |2' - 6" |5' - 6" |8' - 0" |AWNING

| 2' - 0" | 3' - 0" | 5' - 0" | 8' - 0" | CASEMENT

|3' - 0" |5' - 0" |3' - 6" |8' - 6" |SINGLE HUNG

|3' - 0" |5' - 0" |3' - 6" |8' - 6" |SINGLE HUNG

|3' - 0" |5' - 0" |3' - 6" |8' - 6" |SINGLE HUNG

| 3' - 0" | 5' - 0" | 3' - 6" | 8' - 6" | SINGLE HUNG

| 3' - 0" | 5' - 0" | 3' - 6" | 8' - 6" | SINGLE HUNG

| 3' - 0" | 5' - 0" | 3' - 0" | 8' - 0" | SINGLE HUNG

| 3' - 0" | 5' - 0" | 3' - 6" | 8' - 6" | SINGLE HUNG

LEVEL 2 DOOR SCHEDULE

| 3' - 0" | 3' - 6" | 4' - 0" | 7' - 6" | FIXED

| 3' - 0" | 3' - 6" | 4' - 0" | 7' - 6" | FIXED

Count | Width | Height | Operation | Comments |

|2' - 6" |6' - 8" |SINGLE

2' - 8" | 6' - 8" | SINGLE

|2' - 6" |6' - 8" |SINGLE

| 6' - 0" | 6' - 8" | SLIDING

|2' - 8" |6' - 8" |SINGLE

2' - 6" | 6' - 8" | SINGLE

|2' - 8" |6' - 8" |SINGLE

|6' - 0" |6' - 8" |SLIDING

2' - 6" | 6' - 8" | SINGLE

2' - 8" | 7' - 6" | SINGLE

2' - 6" | 6' - 8" | SINGLE

2' - 6" | 6' - 8" | SINGLE

2' - 4" 0' - 0" SLIDING

3' - 0" | 6' - 8" | DOUBLE

2' - 6" | 6' - 8" | SINGLE


| 3' - 0" | 5' - 0" | 3' - 0" | 8' - 0" | SINGLE HUNG

| 3' - 0" | 5' - 0" | 3' - 0" | 8' - 0" | SINGLE HUNG

| 3' - 0" | 5' - 0" | 3' - 0" | 8' - 0" | SINGLE HUNG

Width | Height | Height | Height |

LEVEL 2 LIVING AREA = 981 SF BONUS LOFT AREA = 285 SF



WALL LEGEND

PROPOSED STUD WALL

EXISTING WALL TO REMAIN

□ □ □ □ WALL TO BE DEMOLISHED

PROPOSED PARTIAL HEIGHT WALL

EXISTING / PROPOSED CONCRETE WALL



DESCRIPTION	2ND DESIGN	3RD DESIGN	DESIGN SET	PLANNING SUBMITTAL	PLANNING RESUBMITTAL
DATE	09/12/2019	10/02/2019	11/06/2019	01/28/2020	03/22/2020
REV	2	3	4	9	9
			>	_	

N OF NEW 2-STORY Y HOME WITH RAGE ON VACANT PRC CO SIN ATI

PROJECT NAME:

NEW SINGLE FAMILY HOM
RUSSELL RESIDENCE


TBD 10TH STREET MONTARA, CA 94037

SHEET TITLE

NEW LEVEL 2 FLOOR PLAN

SHEET

A2.2



PROJECT NAME:

NEW SINGLE FAMILY HOME

RUSSELL RESIDENCE

NEW ROOF PLAN

TBD 10TH STREET
MONTARA, CA 94037

SHEET


A2.3

SECTION	DIMENSIONS	AREA
A	18'-1.5" x 44'	797.5 SF
В	23'-3.5" x 20'-3.5"	472.5 SF
С	20'-8.5" x 10'-8.5"	222 SF
D	22'-3.5" x 13'	290 SF
E	1'-7" x 10'-8.5"	17 SF
F	5' x 22'-11.5"	115 SF

LEVEL 1 / GARAGE FLOOR AREA = 1,914 SF

180 SF 10' x 18'

22' - 11 1/2"



1) LEVEL 1 FLOOR DIAGRAM 1/4" = 1'-0"

SECTION	DIMENSIONS	AREA
G	15'-7.5" x 3'-1"	48 SF
Н	17'-10" x 27'-3.5"	486.5 SF
I	15'-7.5" x 3'-1"	48 SF
J	10'-8.5" x 19'-10"	212.5 SF
K	6'-3.5" x 12'	75.5 SF
L	21' x 11'-7.5"	244 SF
M	17' x 2'	34 SF
N	13'-1" x 4'-3"	55.5 SF
0	9'-9" x 6'-3.5"	61.5 SF

LEVEL 2 / LOFT FLOOR AREA = 1,265.5 SF

TOTAL FLOOR AREA = 3,179.5 SF



2 LEVEL 2 FLOOR DIAGRAM 1/4" = 1'-0"

DESCRIPTION	2ND DESIGN	3RD DESIGN	DESIGN SET	PLANNING SUBMITTAL	PLANNING RESUBMITTAL
DAIE	09/12/2019	10/07/2019	11/06/2019	01/28/2020	03/25/2020
KEV	2	3	4	5	9
			VOTO	HH	VACANI


SHEET TITLE

FLOOR AREA DIAGRAMS



THE FACADE ARTICULATION OPTION OF THE COASTSIDE DESIGN GUIDLINES IS BEING UTILIZED.

NOTE:



	I	Ī	į	ı	
ı					ı
				}	

2 09/12/2019	09/12/2019	2ND DESIGN
3 10/07/2019	10/07/2019	3RD DESIGN
4 11/06/2019	11/06/2019	DESIGN SET
5 01/28/2020	01/28/2020	PLANNING SUBMITTAL
6 03/25/2020	03/25/2020	PLANNING RESUBMITTAL

CT SCOPE:
TRUCTION OF NEW 2-STORY
E FAMILY HOME WITH
CHED GARAGE ON VACANT

PROJECT NAME:

NEW SINGLE FAMILY HOME
RUSSELL RESIDENCE


TBD 10TH STREET MONTARA, CA 94037

SHEET TITLE

NEW FRONT AND RIGHT **ELEVATIONS**


SHEET

A3.1



NOTE:

THE FACADE ARTICULATION OPTION OF THE COASTSIDE DESIGN GUIDLINES IS BEING UTILIZED.



2 NEW LEFT ELEVATION 1/4" = 1'-0"

	7	09/12/2019	2ND DESIGN
	က	10/07/2019	3RD DESIGN
E: ON OF MEW 2 STODY	4	11/06/2019	DESIGN SET
LY HOME WITH	5	01/28/2020	PLANNING SUBMITTAL
AKAGE ON VACANI	9	03/25/2020	PLANNING RESUBMITTAL

PROJECT NAME:

NEW SINGLE FAMILY HOME:

RUSSELL RESIDENCE

SHEET TITLE

NEW REAR AND LEFT ELEVATIONS

TBD 10TH STREET MONTARA, CA 94037

SHEET

A3.2

